

LX-1700/2 AUDIO/VIDEO TRANSMITTER

1.7 GHz

The new 1.7 GHz Audio/Video transmitter is a special design for Military applications capable to work in extremely low or high temperature range. This transmitter has 8 easy to change channels and 2 W RF power.

LX-1700/2 works from 10 V- 16 V.



FEATURES:

- 2 W RF Power
- 1700 MHz band
- SMA antenna connector
- RCA audio/video input
- Excellent picture quality
- Long range 7 miles from the air
- Recommended receiver VRX-1700

Technical Specifications	LX-1700/2
Operating Frequencies:	1730 MHz-1850 MHz
Channel:	Agile channels from 1-8
DC Voltage:	12 V – 14 V
RF power:	2 W
Minimum required voltage:	10 V
Battery power:	12 V
Video distortion:	3%
Maximum range:	Long range, over 7 km LOS
Video Format:	PAL, NTSC
Current Consumption:	1000 mA / 12 V
Antenna:	N/A
Antenna Connector:	SMA
Impedance:	50 ohms
Audio input:	300 mV
Video/Audio Connectors:	RCA F
Video Impedance:	75 ohms
Video level:	1 V
Temperature Range: -	40 +78 °C
Dimensions:	6" X 3 " X 1"
Weight:	350 grams
Modulation:	WFM



www.rf-video.com,
Email to: info@rf-video.com.
Copyright. © 2002-2012