

LX-1700/5M AUDIO/VIDEO TRANSMITTER

1.7 GHz

SPECIAL EDITIN

The new 1.7 GHz Audio/Video transmitter is a special design for Military applications capable to work in extremely low or high temperature range. This transmitter has 8 easy to change channels and 5 W RF power. It works from 12 V- 16 V.



FEATURES:

- 5 W RF Power
- 1700 MHz band
- SMA antenna connector
- RCA audio/video input
- Excellent picture quality
- Long range 16 miles from the air
- Recommended receiver VRX-1700

Technical Specifications	LX-1700/5M
Operating Frequencies:	1730 MHz-1850 MHz
Channels selection:	On board selectable
DC Voltage:	12 V
RF power:	5 W
Minimum required voltage:	10 V
Battery power:	12 V
Video distortion	3%
Maximum range:	16 miles from the AIR
Video Format:	PAL, NTSC
Current Consumption:	2000 mA / 12 V
Antenna:	N/A
Antenna Connector:	SMA
Impedance:	50 ohms
Video Connector:	RCA F or open wire
Video Impedance:	75 ohms
Video level:	5 V
Audio level:	300 mV
Temperature Range:	-40 +78 °C
Dimensions:	6" X 3 " X 1"
Weight:	350 grams
Modulation: WFM	WFM



www.rf-video.com,
Email to: info@rf-video.com.
Copyright. © 2002-2008