

LX-5800/2 AUDIO/VIDEO TRANSMITTER

5.8 GHz

The new 5.8 GHz Audio/Video transmitter is a high power audio video transmitter made for Military applications capable to work in extremely low or high temperature range. This transmitter has 8 channels and 2 W RF power. It works from 9 V- 16 V.



FEATURES:

- 2 W RF Power
- 5800 MHz band
- SMA antenna connector
- Excellent picture quality
- Long Range
- Recommended receiver VRX-58I

Technical Specifications	LX-5800/2
Operating Frequencies:	5700 MHz- 5800 MHz
Number of Channels:	8
DC Voltage:	9 V – 16 V
RF power:	2 W
Minimum required voltage:	9 V
Battery power:	12 V
Video distortion:	5%
Maximum range:	LONG RANGE
Video Format:	PAL, NTSC
Current Consumption:	900 mA / 12 V
Antenna:	N/A
Antenna Connector:	SMA
Impedance:	50 ohms
Video Connector:	RCA Female
Video Impedance:	75 ohms
Video level:	1 V
Temperature Range:	-20 +75* C
Dimensions:	6" X 3 " X 1"
Weight:	350 grams
Modulation:	WFM



www.rf-video.com,
Email to: info@rf-video.com.
Copyright. © 2002-2012