

# LX-900B/25 VIDEO TRANSMITTER

# 900 MHz

LX-900B/25 is a single channel audio/video transmitter for 900 MHz. LX-900B/25 is using negative AM modulation same as a broadcast TV. Tested RF power is 25 W. This transmitter is extremely stable. It has built-in VSWR and temperature protection as well. This unit is available for Law enforcement and military.

## 25 W VIDEO TRANSMITTER



## FEATURES:

- 916.6 MHz
- N type antenna connector
- 24 V battery operated
- RCA video input
- Excellent picture quality
- Very long range
- Recommended receiver DCV-900

Technical Specifications	LX-900B/ 25
Operating Frequencies:	916.6 MHz, 906 MHz
Channel:	# 1, 2
DC Voltage:	24 V
RF power:	25 W
Minimum required voltage:	22 V
Battery power:	24 V
Video distortion:	5%
Maximum range:	N/A
Video Format:	PAL, NTSC
Current Consumption:	6 A / 24 V
Antenna:	N/A
Antenna Connector:	N type
Impedance:	50 ohms
Video Connector:	RCA F
Video Impedance:	75 ohms
Video level:	1 V
Temperature Range:	-40 +75* C
Dimensions:	6.5" X 4.0 " X 2.0"
Weight:	650 grams
Modulation:	Negative AM



[www.rf-video.com](http://www.rf-video.com),

Email to: [info@rf-video.com](mailto:info@rf-video.com).

Copyright. © 2002-2005