

The PT-58 is a high-performance Compact Backfire WiFi Antenna that provides 17 dBi gain with a 25° beam-width for directional 5.8GHz ISM and UNII band applications. The weather resistant composite radome houses the "Backfire" reflector which is designed to minimize interference. This antenna can be oriented for either vertical or horizontal polarization.

**Rugged and Weatherproof**

The compact size of this antenna helps minimize wind loading and the rugged, weatherproof construction ensures years of reliable operation. This antenna is supplied with a 60 degree tilt and swivel mast mount kit.



Electrical and Mechanical Specifications	
<b>Frequency</b>	5725 - 5875 MHz
<b>Gain</b>	17 dBi
<b>Horizontal Beam Width</b>	25 degrees
<b>Vertical Beam Width</b>	25 degrees
<b>Connector</b>	Integral N Female
<b>VSWR</b>	< 1.5:1 avg.
<b>Impedance</b>	50 Ohm
<b>Max. Input Power</b>	20 Watts
<b>Weight</b>	2 lbs. (0.9 kg)
<b>Dimensions</b>	9.7" (246 mm) x 2.2" (56 mm)
<b>Mounting</b>	2" (50.8 mm) dia. mast max.
<b>Radome Material</b>	UV-inhibited Polymer
<b>Operating Temperature</b>	-40° C to 85° C (-40° F to 185° F)
<b>Front to Back Ratio</b>	> 25 dB
<b>Lightning Protection</b>	DC Ground
<b>Polarization</b>	Vertical and Horizontal

## RF Antenna Gain Patterns

