

VRX-24LTS/M AUDIO/VIDEO RECEIVER

2.4 GHz

The newest Military Grade 2.4 GHz Audio/video receiver VRX-24LTS/M has excellent performances and it is the most sensitive receiver for 2.4 GHz band on the market! VRX-24LTS/M has fully tunable function in 2.2 GHz - 2.50 GHz frequency range. Video output is 75 ohms standard for any TV monitor. VRX 24LTS/M has built-in sound demodulator. The power supply is 9-12V/200 mA. Antenna connector is an SMA type. The VRX-24LTS is excellent solution for mobile use. You can easy and fast scan all video/audio transmitters in 2.4 GHz band by connecting this receiver to any TV monitor.



FEATURES:

- 2.4 GHz Wideband
- Fully tunable in 2.4 GHz band
- SMA antenna connector
- 12 V battery operated
- RCA audio/video outputs
- Excellent picture quality
- High sensitivity
- Portable operations

Technical Specifications	VRX-24LTS/M
Operating Frequencies:	Tunable frequencies all band 2.4 GHz
Channel:	Any
DC Voltage:	12 V
RF power:	N/A
Minimum required voltage:	10 V
Battery power:	12 V/ 330 mA
Video distortion:	3%
Sensitivity:	-102 dBm (special LNA preamp buit-in)
Video Format:	PAL, NTSC
Current Consumption:	330 mA / 12 V
Antenna:	Recommended high gain, omni directional ant.
Antenna Connector:	SMA
Impedance:	50 ohms
Video output Connector:	RCA F
Video Impedance:	75 ohms
Audio outputs:	300 mV RCA
Carrier frequencies for audio channels:	6 MHz and 6.5 MHz
Temperature Range:	-20 +70* C
Dimensions:	4.5" X 3.6" X 1"
Weight:	230 grams



www.rf-video.com,
2028 Yonge st, Toronto, Ont M4S 1Z9
Email to: info@rf-video.com.
Copyright. © 2002-2005