

VRX-24LZ AUDIO/VIDEO RECEIVER

2.4 GHz

The new Military Grade 2.4 GHz Audio/video receiver VRX-24LZ has excellent performances and it is the most sensitive receiver for 2.4 GHz band on the market! VRX-24LZ has 8 selectable channels in 2.30 GHz - 2.50 GHz frequency range. The power supply is 9-12V/300 mA. Antenna connector is an SMA type. The VRX-24LZ also can be used as a receiving part for a repeater station. Model VRX-24LZ has built-in filters for 2.4 GHz band and IF bandwidth is 16 MHz.



FEATURES:

- 2.4 GHz Wideband
- 8 Selectable channels
- SMA antenna connector
- 12 V battery operated
- RCA video/audio outputs
- Excellent picture quality
- High sensitivity
- Durable metal box

Technical Specifications	VRX-24LZ
Operating Frequencies:	2300 MHz- 2500 MHz
Channel:	#1, 2, 3, 4, 5, 6, 7, 8
DC Voltage:	9 V- 12 V
RF power:	N/A
Minimum required voltage:	9 V
Battery power:	12 V/ 300 mA
Video distortion:	3%
Sensitivity:	-92 dBm
Video Format:	PAL, NTSC
Current Consumption:	280 mA / 9 V
Antenna:	Recommended high gain, omni directional ant.
Antenna Connector:	SMA
Impedance:	50 ohms
Video output Connector:	RCA F
Video Impedance:	75 ohms
Two Audio outputs:	300 mV each channel
Carrier frequencies for audio channels:	6 MHz and 6.5 MHz
Temperature Range:	-10 +65* C
Dimensions:	5.7" X 2.5" X 0.8"
Weight:	200 grams



www.rf-video.com,
2028 Yonge st, Toronto, Ont M4S 1Z9
Email to: info@rf-video.com.
Copyright. © 2002-2005