

VRX-24S VIDEO RECEIVER

2.4 GHz

This is an incredible RF product- the World's smallest 8 channels 2,4 GHz video receiver with amazing sensitivity and easy to use unit- specially made for video surveillance applications. It has a direct video output to the any TV monitor. The antenna connector is an SMA type. The power supply requirement for this receiver is extremely wide- this receiver works from 9 V - 16 V / 280 mA.



FEATURES:

- 2.4 GHz Wideband
- 8 Selectable channels
- SMA antenna connector
- 9 V-12 V battery operated
- RCA video output
- Excellent picture quality
- High sensitivity

Technical Specifications	VRX-24S
Operating Frequencies:	2300 MHz- 2500 MHz
Channel:	#1, 2, 3, 4, 5, 6, 7, 8
DC Voltage:	9 V- 14 V
RF power:	N/A
Minimum required voltage:	9 V
Battery power:	12 V/ 300 mA
Video distortion:	3%
Sensitivity:	-92 dBm
Video Format:	PAL, NTSC
Current Consumption:	280 mA / 9 V
Antenna:	Recommended high gain, omni directional ant.
Antenna Connector:	SMA
Impedance:	50 ohms
Video output Connector:	RCA F
Video Impedance:	75 ohms
Audio output:	N/A
Carrier frequencies for audio channels:	N/A
Temperature Range:	-20 +65* C
Dimensions:	2.5" X 3 " X 1"
Weight:	75 grams



www.rf-video.com,
2028 Yonge st, Toronto, Ont M4S 1Z9
Email to: info@rf-video.com.
Copyright. © 2002-2005